Simple technology...

Cuts your fuel bill up to or more

No chimney? No power vent? NO PROBLEM!

See Page 3.

Introducing . . .

Resolute RT



 Proven 30 year boiler design with lifetime limited warranty* Provides nearly endless hot water!

Proudly made in the USA!

Whisper quiet operation

 Serviceable with stock parts!

4 ways

Resolute RT outlasts



and outperforms other boilers.



The Flow! Delivering more hot water using less energy.

The Energy Kinetics boiler design combines heat and hot water into one unit.

Energy Kinetics hot water tanks use a high-performance plate heat exchanger that allows the tanks to completely heat from the top down with the energy in the boiler. Our tanks finish hot and fully charged, and the boiler finishes with no wasted heat.

Resolute RT

Silent burner cover for whisper quiet operation.

Hard water? Add a scale stopper for reliable operation (up to 25 grains of hardness) without cleaning!

keeps Resoulte RT

off the cold floor.

Attractive venting options!



Chimney or sidewall direct venting. Installs with polypropylene venting!


Energy Kinetics systems can be installed with or without a chimney!

Many homeowners, planning to save money by upgrading or converting to another fuel, sometimes find themselves faced with additional cost of re-lining an aging chimney!

Energy Kinetics' revolutionary designs run clean and relatively cool, allowing for safe venting directly through the wall. This can save thousands of dollars on costly chimney upgrades.

You can also vent our Resolute[™] boilers up through an existing chimney with a cost effective polypropylene chimney lining system.

Resolute RT Installation Dimensions



Recommended service clearance: 20" from front door face, 5" left side and 12" right side. Clearance to combustibles: 4" from the rear cover; 10" above top cover; 0" from polypropylene pipe; 0" for all the other dimensions.

Included (factory piped and assembled): Boiler base, blocked intake, blocked vent and stack high limit, dynamic air elimination manifold, ON/OFF switch and junction box, 3/4" drain valve, plate heat exchanger on hot water models, hydronic Y-strainer, circulator flanges and door safety switch.

Included (field install):

Clean in place valves, relief valve and hydronic circulator (wiring included).

Draft regulator not required or recommended due to advanced combustion chamber.

RESOLUTE RT OIL SPECIFICATIONS

Input	Output	Domestic Hot Water*
.68 GPH	86,500 BTU/Hr.	175 Gal/Hr.
.74 GPH	94,000 BTU/Hr.	186 Gal/Hr.
.85 GPH	108,000 BTU/Hr.	208 Gal/Hr.
1.00 GPH	127,000 BTU/Hr.	238 Gal/Hr.

*Domestic hot water rating based on first hour draw with 77°F rise and 40 gallon tank. Energy converter weight 315 lbs.

RESOLUTE RT GAS SPECIFICATIONS

HEODEOTE III GAO OI EOII IOATIONO		
Input BTU/Hr.	Gross Output BTU/Hr.	Domestic Hot Water
80,000	72,000	152 Gal/Hr.
100,000	89,500	180 Gal/Hr.
150,000	133,500	248 Gal/Hr.

*Domestic hot water rating based on 77° F rise. Not for comparison with tankless boiler ratings.

"Tankless coil ratings overstate hot water delivery, using a misleading short five minute flow test. They just can't keep up with Resolute RT's continuous flow."

Resolute RT

Weight	395 lbs.
Water Content	3 gallons
Air Inlet Pipe Size	3" PVC
Boiler Flue Outlet [†]	3" polypropylene
Poly Chimney Liner	3"
Hydronic Supply	1"
Hydronic Return	1"
Hot Water Supply	3/4"
Hot Water Make-up	3/4"
Hydronic Circulator	Taco 007e

Dimension "A" (On chart at left)		
Burner		
Carlin EZ-1	9.5"	
Carlin EZ-Gas	15.25"	



Accel CS™

For higher efficiency in gas only applications, look at Accel CS.

Or, if you have a properly lined conventional chimney, consider System 2000.

> Scan code below to see all boilers.







Energy Kinetics / System 2000[®]

51 Molasses Hill Road, Lebanon, NJ 08833 (800) 323-2066 Fax (800) 735-2068

visit www.energykinetics.com











AFUE

Your trusted alternative to AFUE industry listings.